




GENERAL SPECIFICATIONS

Category	Sub-category
Stone	Marble
	Type of product
	PVC
Width	Length
122 cm	20 m
Adhesive	Acrylic PSA with air release system
Warranty	10
Stretchable	Stretchable
Resistance to scratch	High
Pattern direction	-
Thickness (average by category)	400 - 450 µm
Storage condition (maximum 3 years from delivery)	5° C - 30° C
Installation method	Dry
Installation area	Interior
Installation temperature	12° C - 38° C
Installation method (ABBA - ABAB)	ABAB



CERTIFICATIONS

CE Wallcovering (EN15102)	Compliant	Color fastness to rubbing (ISO 105-X12) - Assessment according to grey scales	Not tested
REACH	Compliant		
Aldehydes after emission (CMR ISO 16000)	Not tested	Color fastness to shampooing (ISO 18168)	Not tested
Volatile Organic Compounds Testing (EN16516)	Not tested	Color fastness to water (ISO 105-E01)	Not tested
Fire rating (EN13501-1)	D-s2,d0	Liquid absorbency capacity (ISO 9073-6 2000)	Not tested
Wall covering - specification for cork roll (EN13085)	Not required	Liquid wicking rate (ISO 9073-6 2000)	Not tested
IMO/MED Modul B - E	Not tested	Dimensional stability (ISO 3759) - 24h at 50° C - 65% humidity	Not tested
RAIL (ISO 5658 - 2:2006 + A1:2011)	Not tested	Heat and thermal cycle resistance	Not tested
Stain resistance (Tchibo)	Not tested	Color fastness to light	Not tested
Antibacterial properties JIS Z 2081 am. 1 (2012)	Not tested	Adhesion Test	Tested
Spongeability (EN12956)	Not tested	Moisture resistance	Not tested
Washability (EN12956)	Not tested		
Scrubability (EN12956)	Not tested		

CARE AND MAINTENANCE

DURABILITY:

This product offers exceptional resistance to water, dirt, abrasion, UV rays and wear (yellowing, cracking, scaling, delamination).

MAINTENANCE:

For daily care, use a mild soap or pH-neutral detergent to clean the film's surface. Avoid using products with extremely acidic or basic pH levels, as they can harm the material. When cleaning the film surface, only use soft cloths or sponges to prevent any damage. For stubborn stains, apply hot water (not boiling) to the affected area. If necessary, use a solution of 70% isopropyl alcohol, 30% water for cleaning. However, refrain from using this solution on printed film surfaces. For sanitizing, use only isopropyl alcohol-based products like Isopropyl Alcohol Wipes (not for daily use). Avoid organic-based cleaners like ammonia or polish, as they can damage vinyl. Test any cleaning detergents, bactericides, or virucidal products on a hidden area first to ensure compatibility. For Cork Prestige references, minimal cleaning and care are required due to their natural resistance to dust and dirt. Use a brush with gentle bristles to clean. In case of wet or damp stains, use an absorbent cloth to wipe away the moisture and promptly and thoroughly dry the affected area. These recommendations will maintain the film's appearance and extend its lifespan. Persistent stains may indicate inadequate care, in which case, consider using a patch repair method (not guaranteed but effective and economical) or replacing the entire vinyl.

Non-contractual visuals and data, Cover Styl reserves the right to change the composition of its films at any time. The rendition of the colours and finishes on the computer may vary according to the screen and not give a true representation of the true appearance. We therefore recommend you order a sample on line or contact us so that we can examine the finish that best adapts to your requirements. Due to the slight differences in colour in production runs, we advise you to purchase the amount you require in one go to avoid any difference in appearance in the execution of your Cover Styl project.